

MK Edge SRL

GUARDIAN
FALL PROTECTION
PERFORMANCE SAFETY GEAR

Part #	Size	Description
10917	50'	3/16" MK Galvanized Cable SRL w/Swivel Top & High Strength Snap Hook
10918	65'	3/16" MK Galvanized Cable SRL w/Swivel Top & High Strength Snap Hook
10937	50'	3/16" MK Stainless Steel Cable SRL w/Carabiner, Swivel Top, Snap Hook, & Tag Line
10938	65'	3/16" MK Stainless Steel Cable SRL w/Carabiner, Swivel Top, Snap Hook, & Tag Line

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.1-07, and ANSI A10.32-2012 regulations.

Custom configurations available. Contact customer service for details.

MK Edge SRL is suitable for the following applications:



Personal Fall Arrest: MK Edge SRLs may be used in Personal Fall Arrest applications as a component of a MAXIMUM 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. No free fall is permitted, unless used in combination with shock absorber extension. Maximum 2' free fall when used with shock absorber extension. SRL must always be positioned at or above harness dorsal D-ring, or a maximum 2' below harness dorsal D-ring when used with shock absorber extension. Applicable D-ring: Dorsal.



Restraint: MK Edge SRLs may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

For all applications: worker weight capacity range (including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs. if deemed permissible by a Competent Person and used in combination with equipment explicitly certified for such use.

Materials: stainless steel, brass, and aluminum.

NEVER for use in Leading Edge (LE) applications, unless used in combination with shock absorber extension. Suitable for horizontal use when used with shock absorber extension.

May be used in stationary applications only. Attach SRL carabiner to selected anchorage connector, and attach snap hook to applicable harness D-ring.

MAXIMUM 1 user per MK Edge SRL.

UPC-A Codes:

10917: 6 7242110917 6 10918: 6 7242110918 3

10937: 6 7242110937 4 10938: 6 7242110938 1



Repairable by the manufacturer. Contact customer service for details.