

# PRODUCT SPECIFICATIONS



## 6' Restraint Lanyard Adjustable

#82093

### Features

- StayPut buckle allows adjustment from 4-1/2'-6'.
- 1" polyester webbing has a tensile strength of 9,800 lbs.
- Double-locking snap hook at the attachment end and anchorage end rebar hook.

### Material Specifications

<b>Webbing:</b>	<i>Webbing; polyester; Min. 8,500 lbs tensile strength</i>
<b>Adjuster:</b>	<i>Alloy Steel; Min. 3,375 lbs tensile strength</i>
<b>Connector:</b>	<i>Alloy Steel; Min. 5,000 lbs tensile strength</i>
<b>Connector Gates:</b>	<i>Alloy Steel; Min. 3,600 lbs. front and side load</i>

### Performance Specifications

<b>Tensile Strength:</b>	<i>Min. 5,000 lbs.</i>
<b>Max. Capacity:</b>	<i>425 lbs.</i>

### Relevant Standards

<b>OSHA:</b>	<i>CFR1926.502, CFR1910.66</i>
<b>ANSI:</b>	<i>A10.32-2004, Z359.1-2007 Z359.12-2009</i>

### Warnings

- Read, understand and follow all labels and instructions prior to use.
- Inspect before each use.
- Remove from service if there is evidence of damage or excessive wear.
- Never attach a Restraint Lanyard to the front or side D-Rings.



FallTech 1306 S. Alameda St. Compton, CA 90221 Tele: 323-752-0066 [www.falltech.com](http://www.falltech.com)

WARNING: THIS SPECIFICATION SHEET PROVIDES AN OVERVIEW OF PRODUCTS AVAILABLE FROM FALLTECH. CARE HAS BEEN TAKEN TO ASSURE THE ACCURACY OF THE INFORMATION. IT DOES NOT PROVIDE IMPORTANT PRODUCT WARNINGS AND INSTRUCTIONS. FALLTECH RECOMMENDS ALL USERS OF FALL PROTECTION EQUIPMENT UNDERGO THOROUGH TRAINING, AND THAT ALL WARNINGS AND INSTRUCTIONS PROVIDED WITH THESE PRODUCTS BE THOROUGHLY READ UNDERSTOOD PRIOR TO USE. FAILURE TO READ AND FOLLOW ALL PRODUCT WARNINGS AND INSTRUCTIONS COULD RESULT IN SERIOUS INJURY OR DEATH.