VERSATILE ANCHOR FOR FLAT OR SLOPED WOOD AND METAL DECKING



TRUSTED, QUALITY FALL PROTECTION

PRODUCT SHEET

360 DEGREE ROTATION

PROVIDES MAXIMUM MOBILITY

Performance and Value

The Protecta® Metal/Wood Swiveling Roof Anchor is designed to be a removable and reusable anchor for residential or commercial wood and metal frame structures. The rugged design is durable and can withstand the rigors of use from jobsite to jobsite.

- Allows for 360 degree rotation and unrestricted access on rooftops
- Portable and reusable design provides added versatility
- Can be installed on a flat or sloped roof
- Meets the latest OSHA and ANSI standards

Easy to Install and Maintain

Wood Roof Frame

- Position anchor on roof so eight of the lag screw holes are centered over a roof (framing) member
- 2) Install eight 1/4-14 x 2-1/2-inch or longer lag screws

Metal Roof Frame

- 1) Place wood spacers in troughs of decking material to allow anchor to sit level
- 2) Position anchor on roof so eight screw holes line up with center of the top flange of the Z-purlin
- 3) Install eight 1/4-14 x 2-1/2-inch self-drilling screws


Steel Decking

- Place wood spacers in troughs of decking material to allow anchor to sit level
- 2) Position anchor on roof so eight screw holes line up with center of a decking rib
- 3) Install sixteen 1/4-14 x 2-1/2-inch self-drilling screws (8 in each direction)

Dismantling - To remove, unscrew the lag screws and remove from the roof. The roof anchor is removable and designed to be reinstalled following inspection

Important: See User Instruction Manual for Detailed Instructions

Swiveling Design Allows for 360 degree rotation and unprohibited movement Self Retracting Lifeline Provides easy to use full protection for a large work area, must order separately 2190011



2190011 - Metal/Wood Swiveling Roof Anchor

NOTE: In Canada, order model 2190013

Specifications:

Material: Steel

Finish: Black E-coat paint, Zinc plating

Weight: 13 lbs (5.9kg)

Size: 10" x 10" x 3/16" (25.4cm x 25.4cm x .48cm)

Capacity: 420 lbs (190.5kg) (one person)



Capital Safety - USA: 800 328 6146

Canada: 800 387 7484 | Latin America: +1 651 385 4301 Asia: +65 65587758 | Germany: +49 (0)30 92 03 83 87 00 New Zealand: 0800 212 505 | Australia: 1800 245 002 Europe, Middle East, Africa: +33 (0)4 97 10 00 10 Northern Europe: +44 (0)1928 571324

www.capitalsafety.com | info@capitalsafety.com