

# Parapet Clamp

## Part #: 15170

Compliant with all OSHA 1910 and OSHA 1926 Subpart M.

Custom configurations not available. Not repairable.  
Contact customer service for details.

Parapet Clamp is suitable for the following applications:



Parapet Clamp Systems may be used in Fall Prevention applications ONLY. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Parapet Clamp Systems set forth in equipment instructions MUST be adhered to. Personal Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.

**Surfaces more than 6' above lower levels require the use of a Fall Prevention or Fall Protection system.**

Materials: powder-coated steel and galvanized steel.

Weight per unit: 15 lbs.

Parapet Clamp can be adjusted to fit parapet walls ranging from 4" - 24" in width. NEVER attempt to attach to parapets of lesser or greater widths.

MINIMUM parapet wall height: 7".

Parapet Clamps may be placed a MAXIMUM of 8' apart.

Clamp Adjuster MUST face in towards work surface.

For use in combination with Universal Guardrail Post (part #: 61133, 61135, or 61136) and 2" x 4" OR 2" x 6" construction grade lumber guardrails. Guardrails must overlap at least 12" at each end.

Competent Person must ensure Parapet Clamp guardrail system will withstand the following minimum forces, applied in a downward and outward direction: Toprail: 200 lbs.; midrail: 150 lbs.

UPC-A Code: 672421151700

**GUARDIAN**  
FALL PROTECTION

